

Fluke 179/EDA2 Combo Kit - Includes Meter and Deluxe Accessories

Fluke 179 True RMS digital multimeter with industrial strength test lead probe kit in a compact lightweight soft case



Models

Model Name Description

Fluke 179/EDA2 Kit

Fluke 179/EDA2 Combo Kit – Includes Meter and Deluxe Accessories

Includes:

- Fluke 179 Multimeter
 80BK-A Integrated DMM Temperature Probe
 Installed 9V battery
 Users' manual
 AC280 SureGrip™ Hook Clips
 TL910 Electronic Test Probes
 TL224 SureGrip™ Insulated Test Leads
 TPAK ToolPak™ Magnetic Meter Hanger
 Soft carry case

Specs

Specifications			
Voltage DC	Accuracy ¹	±(0.09% + 2)	
	Max. resolution	0.1 mV	
	Maximum	1000 V	
Voltage AC	Accuracy ¹	±(1.0% + 3)	
	Max. resolution	0.1 mV	
	Maximum	1000 V	
Current DC	Accuracy ¹	±(1.0% + 3)	
	Max. resolution	0.01 mA	
	Maximum	10 A	
Current AC	Accuracy ¹	±(1.5% + 3)	
	Max. resolution	0.01 mA	
	Maximum	10 A	
Resistance	Accuracy ¹	±(0.9% + 1)	
	Max. resolution	0.1 Ω	
	Maximum	50 ΜΩ	
Capacitance	Accuracy ¹	±(1.2% + 2)	
	Max. resolution	1 nF	
	Maximum	10,000 μF	
Frequency	Accuracy ¹	±(0.1% + 1)	
	Max. resolution	0.01 Hz	
	Maximum	100 kHz	
Temperature	Accuracy ¹	±(1.0% + 10)	
	Max. resolution	0.1°C	
	Range	-40°C / 400°C	
1. Accuracies are best accuracies	for each function		
Environmental Specificati	ons		
Operating temperature	-10°C to +50°C		
Storage temperature	-30°C to +60°C		
Humidity (without condensation)	0% - 90% (0°C - 35°C) 0% - 70% (35°C -50°C)		
Safety Specifications			
Overvoltage category	EN 61010-1 to 1000 V CAT III EN 61010-1 to 600 V CAT IV		
Agency approvals	UL, CSA, TÜV listed and VDE Pending		
Mechanical and General S	pecifications		
Size	43 x 90 x 185 mm		
Weight	420 g		
Warranty	Lifetime		
Battery life	Alkaline ~200 hours typical, without backlight		