

## DK-168000 Flexible current probe

**Product Introduction**

Product Name :	DK-168000 Flexible current probe
Short Description :	DK-168000 Bandwidth Hz-15MHz Accuracy 1% peak-peak current 140000A

**Detailed description :**

Model	DK-168000
Sensitivity mV/A	0.1
Peak-peak Current (A)	140000
Measurement from	15A
DC offset mV	±2
Peak di/dt kA/μs	50
Bandwidth(3db)	5Hz-15MHz
Accuracy	1%
Coil circumference	100, 200 or 1000mm
Coil cross section(max)	3KV
Temperature Range	-20°C-100°C
Cable length(from box to coil)	2m or 4m
Power supply	DC SUPPLY ADAPTOR 6-9V or Battery 4
Integrator box dimensions	H=160mm, W=80mm, D=28mm
Coil cross section(max)	8mm-14mm(with sleeve)
Output socket	BNC(50 Ω)
Min. output loading	1M Ω

Coil circumference: 100, 200 or 1000mm

Coil cross section(max): 3KV

Temperature range: -20°C-100°C

Cable length(from box to coil): 2m or 4m

Power supply: DC supply adaptor or 6-9v or 4 batteries

Integrator box dimension: H=160mm, W=80mm, D=28mm

Coil cross section(max): 8mm-14mm(with sleeve)

Output socket: BNC(50 Ω)

Min. Output loading: 1M Ω