

## TA8020 Temperature/Vane anemometer



TA8020 Temperature/Vane anemometer

- Measure: m/s, km/h, fpm, mph, kts, Beaufort scale, °C, °F
- Resolution: 0.1 m/s, 1 fpm, 0.1°C, 0.1°F
- Range: 0.4~20 m/s, 80~4000 fpm
- Sample Rate: 0.5sec
- Operating temperature: -10~50°C, 14~122°F
- Special function: Auto power off; Data hold; MAX and MIN; Back light
- Dimension: 157 x 60 x 30mm
- Weight: 180g



TA8021 Temperature/Humidity/Vane anemometer

- Measure: m/s, km/h, fpm, mph, kts, Beaufort, %RH, td(dew point temperature), °C, °F
- Resolution: 0.1 m/s, 1 fpm, 0.1%RH, 0.1°C, 0.1°F
- Range: 0.4~20 m/s, 80~4000 fpm, 0~100%RH, -10~50°C, 14~122°F
- Accuracy:  $\pm(2\%$  of reading + 0.3m/s)  
 $\pm(2\%$  of reading + 60fpm)  
 $\pm 3\%$  RH (5~95% RH)  
 $\pm 1^\circ\text{C}$ ,  $\pm 1.8^\circ\text{F}$
- Special function: Auto power off; Data hold; MAX MIN; Back light; Overload display; Low battery indicator
- Dimension: 157 x 60 x 30mm
- Weight: 180g



- TA8022 Temperature/Air volume/Vane anemometer
- Measure: m/s, km/h, fpm, mph, kts, Beaufort, °C, °F, m<sup>3</sup>/s, m<sup>3</sup>/h, CFM, m<sup>2</sup>, ft<sup>2</sup>
  - Resolution: 0.1 m/s, 1 fpm, 0.1°C, 0.1°F, 1m<sup>3</sup>/s
  - Range: 0.4~20 m/s, 0~99999m<sup>3</sup>/s, -10~50°C, 14~122°F
  - Accuracy: ±(2% of reading + 0.3m/s)  
±(2% of reading + 60fps)  
±1°C, ±1.8°F  
±(3% of reading)m<sup>3</sup>/s
  - Special function: Auto power off; Data hold; MAX MIN; Back light; Overload display; Low battery indicator
  - Dimension: 157 x 60 x 30mm
  - Weight: 180g



### Calibration

Accessories included:

- Free 1.5V x3AAA batteries
- Free protect cover
- Free protective carrying case
- Free Wrist Strap
- User's Manual