# UNI-T UT118A

## Pen Type Digital Multimeters

| **Specifications** | **Range** | | **Best Accuracy** |
|---|---|---|---|
| **Model** | **SCAN Mode** | **AUTO Mode** | **UT118A** |
| DC Voltage (V) | 3V/30V/300V | 3V/30V/300V | ±(1%+3) |
| AC Voltage (V) | 3V/30V/300V | 3V/30V/300V | ±(1%+4) |
| Resistance (Ω) | 300Ω/3kΩ/30kΩ/300kΩ/3MΩ | 300Ω/3kΩ/30kΩ/300kΩ/3MΩ/30MΩ | ±(1%+3) |
| Capacitance (F) | 3nF/30nF/300nF/3μF/30μF/300μF | 3nF/30nF/300nF/3μF/30μF/300μF/3mF | ±(3%+5) |
| **Features** | | | |
| Display Count | | | 3000 |
| Auto Range | | | √ |
| Diode | | | √ |
| Auto Power Off | Around 10 Minutes | | √ |
| Continuity Buzzer | | | √ |
| Low Battery Indication | | | √ |
| Data Hold | | | √ |
| MAX Mode | | | √ |
| MIN Mode | | | √ |
| LCD Backlight | | | √ |
| Penlight | | | √ |
| Input Impedance for DCV | ≥10MΩ | | √ |
| **General Characteristic** | | | |
| Power | 3V Li-MnO2 Cion Cell Battery | | |

| | |
|---|---|
| LCD Size | 28mm×14mm |
| Product Color | Red and Grey |
| Product Net Weight | 90g |
| Product Size | 20mm×27mm×182mm |
| Standard Accessories | Battery, Test Lead |
| Standard Individual Packing | Blister, English Manual |
| Standard Quantity Per Carton | 80 PCs |
| Standard Carton Measurement | 570mm×300mm×415mm (0.071 CBM Per Export Carton) |
| Standard Carton Gross Weight | 12.5Kg |