



EN:61010-1  
EN:61326-1  
EN:61010-2-032



■ UT200C



■ UT200D

### SPECIFICATIONS

Specifications	Range	Best Accuracy	
		UT200C	UT200D
Model		UT200C	UT200D
AC Current (A)	60A/600A	± (2%+5)	± (2%+5)
AC Voltage (V)	600V	±(1.2%+5)	±(1.2%+5)
DC Voltage (V)	60V/600V	± (0.8%+3)	± (0.8%+3)
Resistance (Ω)	600Ω/6KΩ/60KΩ	±(1.0%+4)	±(1.0%+4)
Frequency (Hz)	10Hz~60Kz	± (1.0%+4)	± (1.0%+4)
Temperature (°C)	-40 °C ~ 300°C		± (2.0%+8)
<b>Features</b>			
Display Count		5999	5999
Auto Range		✓	✓
Jaw Capacity		28mm	28mm
Diode		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
MAX/MIN		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

### GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	260g
Product Size	210mm × 75.6mm × 30mm
Standard Accessories	UT200C-Battery, Test Lead, Carrying Bag UT200D-Battery, Test Lead, Carrying Bag, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	535mm × 490mm × 330mm (0.087 CBM Per Standard Carton)
Standard Carton Gross Weight	23 Kg