

UT60A

Modern Digital Multimeters



[Enlarge](#)



Registered Design No.: 0011438. 1M002

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	$\pm(0.8\%+1)$
AC Voltage	4V/40V/400V/750V	$\pm(1\%+5)$
DC Current	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1\%+2)$
AC Current	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm(1.5\%+5)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Capacitance	40nF/400nF/4 μ F/40 μ F/100 μ F	$\pm(3\%+5)$
Frequency	10Hz-10MHz	$\pm(0.1\%+3)$
Duty Cycle	0.1%~99.9%	✓
Special Functions		
Fused 10A Range		✓
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
Relative Mode		✓
Data Hold		✓
RS232C		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10M Ω	✓
Max Display	3999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	340g
Product Size	177 x 85 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip, RS232C Interface Cable, Software
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326mm (0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	24.6kg