



FRONTLINE
Safety

DATA SHEET

Unit F, 230 Parkway Point, Springhill Parkway,
Glasgow Business Park, Glasgow, UK, G69 6GA

www.frontline-safety.co.uk

t: +44(0)141 771 7749

e: sales@frontline-safety.co.uk

Xgard IR

Infrared Gas Detector

Fail safe technology

Low cost of ownership

Fast response

Highly versatile



Xgard IR

Infrared Gas Detector

Xgard IR is an explosion-proof gas detector which uses a dual-wavelength infrared sensor to provide highly dependable detection of hazardous gases and vapours. Based on Crowcon's hugely successful Xgard design, Xgard IR offers the many advantages of infrared sensor technology in a rugged and versatile package including; fail safe sensor technology, immune to poisoning, no damage by over-gasing, fast response and suitable for use in inert atmospheres.

Gases and ranges

Gas	LEL LEL (% vol)	STEL UEL (% vol)	Ranges available
Butane (C ₄ H ₁₀)	1.8 (1.4)	9 (9.3)	0-100% LEL
Butene (C ₄ H ₈)	1.6	-	0-100% LEL
Carbon Dioxide (CO ₂)	0.5% vol.	1.5% vol.	0-2 or 0-5%
Ethanol (C ₂ H ₆ O)	3.3 (3.1)	19 (19)	0-100% LEL
Ethylene (C ₂ H ₄)	2.7 (2.3)	36 (36)	0-100% LEL
Hexane (C ₆ H ₁₄)	1.2 (1)	7.4 (8.4)	0-100% LEL
LPG	2	10	0-100% LEL
Methane (CH ₄)	5 (4.4)	15 (17)	0-100% LEL
Methanol (CH ₃ OH)	6.0	-	0-100% LEL
Pentane (C ₅ H ₁₂)	1.5 (1.4)	8 (7.8)	0-100% LEL
Propane (C ₃ H ₈)	2.2 (1.7)	10 (10.9)	0-100% LEL

Specification

Size	H156 x W166 x D111mm (6.1 x 6.5 x 4.3 inches)
Weight	1kg (2.2lbs) Aluminium; 3.1kg (6.8lbs) Stainless Steel
Enclosure material	Corrosion resistant Aluminium or 316 Stainless Steel
Ingress protection	IP65
Cable entries	1 x M20 or 1/2" NPT on right side.
Power	14-32Vdc. < 4W
Operating temperature	-20°C to +55°C (-4°F to 131°F)
Humidity	0 to 95% RH non-condensing
Electrical output	3-wire 4-20mA (current sink or source)
Terminals	Suitable up to 2.5mm ² cable
Sensor type	Infrared
Repeatability	+/- 2% FSD
Zero drift	+/- 2% FSD per year maximum
Response time	T90 <30 secs
Hazardous area zones	Zone 1 and Zone 2, Zone 21 and 22
Approvals	Baseefa04ATEX0024X Ex II 2GD Ex d IIC T6 Gb Ex tb IIIC T80°C Db (-40°C ≤ Tamb ≤ + 50°C) Ex d IIC T4 Gb Ex tb IIIC T110°C Db (-40°C ≤ Tamb ≤ + 80°C) IECEx BAS 05.0043X Ex d IIC T6 Gb Ex tb IIIC T80°C Db (-40°C ≤ Tamb ≤ + 50°C) Ex d IIC T4 Gb Ex tb IIIC T110°C Db (-40°C ≤ Tamb ≤ + 80°C) UL Class 1 Div 1, Groups B, C, D
EMC compliance	EN 50270 FCC Part 15 ICES-003
Performance	EN60079-29-1

Crowcon reserves the right to change the design or specification of the product without notice.

Thank you for reading this data sheet.

For pricing or for further information, please contact us
at our UK Office, using the details below.

Please note — Product designs and specifications are subject
to change without notice. The user is responsible for
determining the suitability of this product.



Unit F, 230 Parkway Point, Springhill Parkway,
Glasgow Business Park, Glasgow, UK, G69 6GA

www.frontline-safety.co.uk

t: +44(0)141 771 7749

e: sales@frontline-safety.co.uk