

AN **aem** BRAND

## 15189 PRECIPITATION SENSOR ACCORDING TO JOSS-**TOGNINI**









## Developed through experience

and equipped with the features and benefits of its proven predecessors, this all-metal Tipping Bucket Precipitation Sensor 15189 is the "best in class". Its functionality is precisely designed to meet the needs of classical meteorology and hydrology as well as semi-professional industrial meteorology. The Precipitation Sensor 15189, in its different variants, is an extremely economical investment.

- · Best price-performance ratio in its class!
- · Single device or part of an automatic weather station
- · Very reliable and robust measuring system
- · High quality materials
- · Easy installation
- · Connectable to Lambrecht's data logger PreLOG, met[LOG] and Ser[LOG]

## **APPLICATIONS**

- · Classical meteorology and hydrology
- · Agriculture meteorology
- · Measuring networks of water suppliers
- · Lysimeter systems
- · Sewage plants

Professional Line	15189
ld-No.	00.15189.002000 Sensor with 2 cm <sup>3</sup> bucket, unheated 00.15189.004000 Sensor with 4 cm <sup>3</sup> bucket, unheated
Measuring range	2 cm <sup>3</sup> : 08 mm/min • 4 cm <sup>3</sup> : 016 mm/min
Accuracy	± 2 % with intensity correction
Resolution	Version with 2 cm <sup>3</sup> tipping bucked: (~2 g) volume of tipping bucket - 0.1 mm Version with 4 cm <sup>3</sup> tipping bucket: (~4 g) volume of tipping bucket - 0.2 mm
Pulse output	Reed contact • polarity protected • bounce-free signal
Switching capacity	Max. 30 VDC / 0.5 A

Continued on page 2





Professional Line	15189
Collection surface	200 cm <sup>2</sup> / WM0 standard
Range of application	0+70 °C (frost resistant down to -20 °C)
Supply voltage	430 VDC
Current consumption	Max. 100 μA • typical 50 μA
Measuring elements	Tipping bucket system • precision stainless steel bucket acc. to Joss-Tognini
Design	Mounting pipe Ø 60 mm
Dimensions	H 292 mm • Ø 190 mm
Housing	Aluminium • anodised
Weight	Approx. 3 kg
Standards	WMO-No. 8 • VDI 3786 page 7 • EN 50081/82 • VDE 0100
Accessories (order separately)	32.15188.060090 Sensor cable 2 pole, 7 m 00.15091.600XXX Windshield according to Tretyakov for measuring height 1 m, 1.5 m and 2 m 32.15180.023020 Bird defense ring 32.15189.008000 Insect filter for 15189 unheated

As of: 13.07.2023