



UT658 USB tester is used to inspect USB charger and portable power source of electronics products. UT658 can output voltage, current, and power. Users can use this device to monitor charging status of any USB powered device.



● UT658

### SPECIFICATIONS

	UT658	UT658B
Input voltage range (V)	3V~9V	3V~9V
Voltage resolution	0.01V	0.01V
Voltage monitoring accuracy	±1%	±(1%+5)
Current monitoring range (A)	0A~3A	0A~3.5A
Current monitoring accuracy	±(1%±2)	±(1%±5)
Current resolution	0.01A	0.01A
Capacity	0~9999MAH	0~39999MAH
Capacity data storage	10 sets	10 sets
Display	LCD	LCD
Warning	√	√
Button	√	√
Cable length		10cm
Pollution level	2	2
Working temperature	0°C~40°C	-10°C~40°C
Storage temperature	-10°C~50°C	-10°C~50°C
Relative humidity	<75%	<75%

### GENERAL CHARACTERISTICS

Product color	White
Product net weight	<b>UT658:</b> 28g; <b>UT658B:</b> 30g
Product size	<b>UT658:</b> 84mm x 29mm x 12mm; <b>UT658B:</b> 72mm x 29mm x 12mm
Standard individual packing	<b>UT658:</b> Blister, insert card; <b>UT658B:</b> Gift box
Standard quantity per carton	<b>UT658:</b> 100pcs; <b>UT658B:</b> 60pcs
Standard carton measurement	<b>UT658:</b> 185mm x 180mm x 185mm; <b>UT658B:</b> 205mm x 170mm x 170mm
Standard carton gross weight	<b>UT658:</b> 3.3kg; <b>UT658B:</b> 2.3kg



● UT658B