

**UT210 SERIES**  
**100A Mini Clamp Meter**  
**UT210E**



**UNI-T**

**Features:**

- AC/DC current
- AC/DC voltage
- Resistance
- Capacitance
- Diode test
- Continuity test
- Max/Min measurements
- Auto ranging
- TRMS
- V.F.C
- N.C.V
- Continuity Buzzer
- Compliance with safety requirements , EN61326-1 EN61010-1 CAT III 300 V / CAT II 600 V
- Zero Mode
- LCD Backlight
- Auto Power OFF
- Jaw Capacity -17mm
- Data Hold



Specifications	Range	Best Accuracy
<b>Model</b>		<b>UT210E</b>
AC Current (A)	2A/20A/100A	± (2.5%+5)
DC Current (A)	2A/20A/100A	± (2%+3)
AC Voltage (V)	2V/20V200V/600V	± (1%+3)
DC Voltage (V)	200mV/2V/20V200V/600V	± (0.7%+3)
Resistance (Ω)	200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ	± (1%+2)
Capacitance (F)	2nF/20nF/200nF/2μF/20μF/200F/2mF/20mF	± (4%+5)
<b>Features</b>		
Display Count		2000
Auto Range		✓
Jaw Capacity		17mm
True RMS		✓
Diode	Around 3.0V	✓
V.F.C.		✓
MAX/MIN		✓
NCV		✓
Data Hold		✓
Zero Mode		✓
LCD Backlight		✓
Auto Power Off	Around 15 Minutes	✓
Continuity Buzzer		✓
Low Battery Indication	≤2.5V	✓
Input Protection		✓
Input Impedance for DCV	≥10MΩ	✓
<b>General Characteristic</b>		
Power	AAA 1.5V × 2	
LCD Size	39.3mm × 26.5 mm	
Product Color	Red and Grey	
Product Net Weight	170g	
Product Size	175mm × 60mm × 33.5mm	
Standard Accessories	Batteries, Test Lead	
Standard Individual Packing	Box, Carrying bag, English Manual	
Standard Quantity Per Carton	40PCs	
Standard Carton Measurement	385mm×345mm×305mm (0.041 CBM Per Standard Carton)	
Standard Carton Gross Weight	11Kg	



**UT210E**