

FLIR CM83 600A True RMS Power Clamp

The FLIR CM83 is an industrial-grade Power Clamp Meter engineered with advanced power analysis and VFD filtering functions required by electrical troubleshooters.

- VFD Mode provides superior accuracy for working on VFD-controlled equipment
- Advanced power efficiency and harmonics measurements for system level performance analysis
- Powerful Worklights not only assist with clamping but are bright enough to serve as a primary worklight
- FLIR Tools Mobile connects the FLIR CM83 to your compatible smartphone and tablet via Bluetooth*
- METERLINK® technology wirelessly integrates electrical readings on your infrared image with METERLINK-enabled FLIR Thermal Cameras

Features:

 Voltage and Current, Bright White LED Backlight, Analog Bargraph, Power Factor, Phase Rotation, Integrated Non Contact Voltage Detector, Min, Max, Average, Auto Power Off, Data Hold, Relative, Peak Hold, DCA Zero, Battery Status

Includes:

• 6 AAA Batteries, User Manual/CD, CAT IV Silicon Test Leads and Limited Lifetime Warranty

TECHNICAL SUMMARY	RANGE	BASIC ACCURACY
AC/DC Current	600A	±2%
AC/DC Voltage	1000V	±1% / 0.7%
Harmonics	1st-25th Order	±5%
Total Harmonic Distortion	0.0 to 99.9%	±3%
Inrush Current	600ACA (Integration Time 100ms)	±3 %
Active Power	10kW to 600kW (10V, 5A min)	±3%
Diode Test	0.4 to 0.8V	±0.1V
Capacitance	3.999mF Max	±1.9%
Resistance	99.99kΩ Max	±1%
Continuity Threshold	30Ω	±1%
Frequency	20.00Hz to 9.999kHz	±0.5%

GENIERAL INIFORMATION

Jaw Opening 1.45in (37mm, 1000MCM)

Category Rating CAT IV-600V, CAT III-1000V

Bluetooth Range Max 32ft (10m)

Warranty Limited Lifetime*

Ordering Information



NASHUA

FLIR Systems, Inc. PH: +1 603-324-7600 PORTLAND Corporate Headquarters FLIR Systems, Inc. PH: +1 866.477.3687 CANADA

FLIR Systems, Ltd. PH: +1 800.613.0507 MEXICO/LATIN AMERICA

FLIR Systems Brasil Av. Antonio Bardella PH: +55 15 3238 8070

NASDAQ: FLIR

 $^{^{\}star}$ See www.flir.com/test for latest compatibility information and more warranty details