

EARTH RESISTANCE METER MRU-200-GPS

**New with
GPS
function!**



MRU-200-GPS is the unique meter in the market which uses all measurement methods.



Possible measurements:

- earth resistance measurement with 2-pole, 3-pole, 4-pole method,
- selective earth resistance measurement with clamp (no influence from parallel earths; no opening of rusty junctions is needed),
- impulse earth resistance measurement, three kinds of measuring impulse 4/10 μ s, 8/20 μ s, 10/350 μ s,
- two clamps earth resistance measurement without auxiliary test probs,
- earth resistivity measurement,
- leakage current measurement,
- built in GPS,
- GPS coordinates of the measurement are stored in meter memory.

Standard accessories of the meter MRU-200-GPS:

- Test lead with banana plug; 1,2 m; red
- Test lead with banana plugs 2,2 m; black
- Test lead on a reel with banana plugs; 25 m red
- Test lead on a reel with banana plugs; 25 m blue
- Shielded test lead on a reel with banana plugs; 50m yellow
- USB transmission cable
- charger for battery loading from the socket of car lighter (12 V)
- Earth contact test probe (rod); 0,30 m - (4 pcs.)

- WAPR1X2REBB**
- WAPR2X2BLBB**
- WAPR025REBBSZ**
- WAPR025BUBBSZ**
- WAPR050YEBBSZE**
- WAPRZUSB**
- WAPRZLAD12SAM**
- WASONG30**
- Carrying case L2
- Ni-MH battery package 4,8 V 4,2 Ah
- „Crocodile” clip K01; black
- „Crocodile” clip K02; red
- Cramp
- Power supply adaptor Z7
- Cable for battery charger
- Hanging straps
- Calibration certificate issued by calibration laboratory

- WAFUTL2**
- WAAKU07**
- WAKROBL20K01**
- WAKRORE20K02**
- WAZACIMA1**
- WAZASZ7**
- WAPRZLAD230**
- WAPOZSZEKPL**

Optional accessories of the meter MRU-200-GPS:

- Hard carrying case
- Earth contact test probe (rod); 0,80 m
- Test lead with banana plugs 2 m (N-1)
- Current clamp C-3 ($\varnothing=52$ mm)
- Current clamp N-1 ($\varnothing=52$ mm)
- Current flexible clamp (Rogowsky coil) F-1 ($\varnothing=400$ mm)

- WAWALX13**
- WASONG80**
- WAPR200DZBB**
- WACEGC3OKR**
- WACEGN1BB**
- WACEGF1OKR**
- Battery case LR14 (size C)
- Carrying case L3
- Adapter ERP-1 for measurement of earth resistance of transmission line pylons

- WAP0J1**
- WAFUTL3**
- WAA0AERP1V2**

Sonel S.A.
Wokulskiego 11
58-100 Świdnica, PL
tel. +48 74 85 83 860
fax +48 74 85 83 809

export@sonel.pl
www.sonel.pl



MRU-200-GPS

• It allows to take the measurements of:

- earthing resistance using auxiliary electrodes,
- earthing resistance using auxiliary electrodes and clamp (for measurements of multiple earthing)
- earthing resistance using double clamps (for measurement of earthing when it is impossible to use auxiliary electrodes),
- impulse earth resistance (without disconnecting measured earthing),
- ground resistivity (Wenner method),
- current using the clamp (e.g. leakage) and flexible clamp (Rogowsky coil),
- measurement of continuity of equipotential bondings and protective conductors (meeting the requirements of IEC 60364-6-61:2000 section 6.12.2) with auto-zero function – with current 200 mA.

• Additionally:

- measurement of resistance of auxiliary electrodes R_s and R_H ,
- measurement of interference voltage,
- measurement of interference frequency,
- measurement in the presence of interference voltage in the power network with frequency 16 2/3 Hz, 50 Hz, 60 Hz and 400 Hz (with automatic selection of proper frequency of measuring signal or with manual selection),
- selection of maximum measuring voltage (25 V and 50 V),
- introducing the distance between the electrodes for the resistivity in metres (m) and feet (ft),
- memory of 990 measurements (10 banks of 99 cells each),
- calibration of clamp used,
- real time clock (RTC),
- data transmission to the computer (USB und Bluetooth),
- indication of battery state.

Electric security:

- type of insulation double, according to EN 61010-1 and IEC 61557
- measurement category CAT IV 300 V acc. to EN 61010-1
- protection class acc. to EN 60529 IP 54

Rated operational conditions:

- operation temperature -10...+50°C
- storage temperature -20...+70°C
- humidity 20...90%

Other technical data:

- LCD display graphic, backlit
- interface USB und Bluetooth
- number of measurements carried out of set of batteries > 1200

Measurement of interference voltage

Range	Resolution	Accuracy
0...100 V	1 V	±(2% m.v. + 3 digits)

Measurement of interference frequency

Range	Resolution	Accuracy
15...450 Hz	1 Hz	±(1% m.v. + 2 digits)

Measurement of earthing resistance (method 3- and 4-pole)

measurement range to IEC 61557-5: **0,100 Ω...19,9 kΩ**

Range	Resolution	Accuracy
0,000...3,999 Ω	0,001 Ω	±(2% m.v. + 4 digits)
4,00...39,99 Ω	0,01 Ω	±(2% m.v. + 2 digits)
40,0...399,9 Ω	0,1 Ω	
400...3999 Ω	1 Ω	
4,00k...19,99 kΩ	0,01 kΩ	±(5% m.v. + 2 digits)

Measurement of earth connection and equipotential bonding (2P)

range of measurements in accordance with IEC 61557-4: **0,045 Ω...19,99 kΩ**

Range	Resolution	Accuracy
0,000...3,999 Ω*	0,001 Ω	±(2% m.v. + 4 digits)
4,00...39,99 Ω	0,01 Ω	±(2% m.v. + 2 digits)
40,0...399,9 Ω	0,1 Ω	
400...3999 Ω	1 Ω	
4,0...19,99 kΩ	0,01 kΩ	±(5% m.v. + 2 digits)

* - in range 0,000...0,045 Ω the accuracy is not specified.

Measurement of resistance of auxiliary electrodes R_H and R_s

Range	Resolution	Accuracy
0...999 Ω	1 Ω	±(5% ($R_s+R_e+R_H$)) + 8 digits)
1,00...9,99 kΩ	0,01 kΩ	
10,0...19,9 kΩ	0,1 kΩ	

Measurement of multiple earthing resistance with using the clamp and auxiliary electrodes (3p + clamp)

measurement range to IEC61557-5: **0,120...1999 Ω**

Range	Resolution	Accuracy
0,000...3,999 Ω*	0,001 Ω	±(8% m.v. + 4 digits)
4,00...39,99 Ω	0,01 Ω	±(8% m.v. + 3 digits)
40,0...399,9 Ω	0,1 Ω	
400...1999 Ω	1 Ω	

* - in range 0,000...0,045 Ω the accuracy is not specified.

Measurement of multiple earthing resistance with using double clamps

Range	Resolution	Accuracy
0,00...19,99 Ω	0,01 Ω	±(10% m.v. + 3 digits)
20,0...149,9 Ω	0,1 Ω	±(20% m.v. + 3 digits)

Measurement of ground resistivity Measurement method: Wenner, $\rho=2\pi LR_e$

Range	Resolution	Accuracy
0,0...199,9 Ωm	0,1 Ωm	depending on measurement accuracy R_e with 4p method, but not less than ±1 digit
200...1999 Ωm	1 Ωm	
2,00...19,99 kΩm	0,01 kΩm	
20,0...99,9 kΩm	0,1 kΩm	
100...999 kΩm	1 kΩm	

L – distance between probes: 1...50 m

Measurement of AC current (leakage)

Range	Resolution	Accuracy
0,1...99,9 mA ¹	0,1 mA	±(8% m.v. + 5 digits)
100...999 mA ¹	1 mA	±(8% m.v. + 3 digits)
1,00...4,99 A ^{1,2}	0,01 A	±(5% m.v. + 5 digits) ¹ unspecified ²
5,00...9,99 A ^{1,2}	0,01 A	±(5% m.v. + 5 digits)
10,0...99,9 A ^{1,2}	0,1 A	
100...300 A ^{1,2}	1 A	

¹ – receiving clamp (diameter 52 mm) – C-3

² – flexible clamp (Rogowsky coil) with diameter 400 mm – F-1

Measurement of dynamic earthing resistance (R_b) with impulse wave method (4 $\frac{1}{2}$)

Range	Resolution	Accuracy
0,0...99,9 Ω	0,1 Ω	±(2,5% m.v. + 3 digits)
100...199 Ω	1 Ω	

choice impulse edges: 4/10 μs, 8/20 μs, 10/350 μs

„m.v.“- measured value