

Model	Sensitivity mV/A	Peak-Peak Current (A)	Min. Current (A)	Noise (mV Pk-Pk)	Bandwidth (3db)	Accuracy
High Sensitivity Ranges of DK flexible current probe						
DK-Mini070	100	70	0.7	12	100Hz-4/8MHz	1%+2mV
DK-Mini140	50	140	1.4	12	100Hz-4/8MHz	1%+2mV
DK-Mini350	20	350	3.5	10	60Hz-4/8MHz	1%+2mV
Middle Sensitivity Ranges of DK flexible current probe						
DK-0700	10	700	7.0	14	5Hz-6/10MHz	1%+3mV
DK-1400	5	1400	14	14	5Hz-15MHz	1%+3mV
DK-3500	2	3500	35	10	5Hz-15MHz	1%+2mV
DK-7000	1	7000	70	8	5Hz-15MHz	1%+2mV
DK-14000	0.5	14000	140	5	5Hz-15MHz	1%+2mV
Standard Ranges of DK flexible current probe						
DK-35000	0.2	35000	350	5	5Hz-15MHz	1%+2mV
DK-70000	0.1	70000	700	5	5Hz-15MHz	1%+2mV
DK-140000	0.05	140000	1400	5	5Hz-15MHz	1%+2mV
DK-350000	0.02	350000	3500	5	5Hz-15MHz	1%+2mV
DK-2000	2	2000	35	10	50Hz-150KHz	2%