

## TR25 Modular RTD thermometer

Comprehensive and common temperature measurement technology for almost all branches of industry



More information and current pricing:

[www.endress.com/TR25](http://www.endress.com/TR25)

### Benefits:

- High degree of flexibility thanks to modular design with standard terminal heads as per DIN EN 50446 and customer-specific immersion lengths
- High degree of insert compatibility and design as per DIN 43772
- Fast response time with reduced tip form
- Head transmitter with easy selection: Analog output 4 to 20 mA, HART®, PROFIBUS® PA or FOUNDATION Fieldbus™

### Specs at a glance

- **Accuracy** class A acc. to IEC 60751 class AA acc. to IEC 60751
- **Response time** depending on configuration  $t_{50} = 2\text{ s}$   $t_{90} = 5\text{ s}$
- **Max. process pressure (static)** at 20 °C: 40 bar (580 psi)
- **Operating temperature range** PT 100: -200 °C ...600 °C (-328 °F ...1.112 °F)
- **Max. immersion length on request** up to 10.000,00 mm (393,70")

**Field of application:** The thermometer is mainly used in the chemical industry but also finds its use in other branches. The device with head transmitter is a complete unit ready for use with enhanced measurement accuracy and reliability compared to directly wired sensors. A variety of process connections, dimensions and materials offer flexible application possibilities.

### Features and specifications

## Thermometer

### Measuring principle

Resistance Temperature Detector

### Characteristic / Application

metric style  
modular temperature assembly  
threaded process connection  
without neck

### Thermowell / protection tube

without (not intended to use with thermowell)

### Insert / probe

mineral insulated (MI), flexible

### Outer diameter protection tube / Insert

6,0 mm (0,24")

### Max. immersion length on request

up to 10.000,00 mm (393,70")

### Material protection tube/ thermowell

1.4404 (316L)

### Optional coating

Not defined

### Process connection

male thread:

G1/4"

G1/2"

NPT1/4"

NPT1/2"

### Tip shape

straight

reduced

## Thermometer

**Surface roughness Ra**

Not defined

**Operating temperature range**

PT 100:

-200 °C ...600 °C

(-328 °F ...1.112 °F)

**Max. process pressure (static)**

at 20 °C: 40 bar (580 psi)

**Accuracy**

class A acc. to IEC 60751

class AA acc. to IEC 60751

**Response time**

depending on configuration

t<sub>50</sub> = 2 st<sub>90</sub> = 5 s**Integration head transmitter**yes (4 ... 20 mA; HART; PROFIBUS PA; FOUNDATION  
FIELDBUS)**Certification**

Gost Metrology

SIL (transmitter only)

More information [www.endress.com/TR25](http://www.endress.com/TR25)