# TU54 Flanged barstock thermowell, US style

# Thermowell with flanged process connections and round extension



More information and current pricing: www.endress.com/TU54

## **Benefits:**

- Extension, immersion length and total length can be chosen according to process requirements
- Modular configuration enable a use in all industrial processes with severe thermal and mechanical stresses
- Fast response time with conical or stepped tip form

# Specs at a glance

- Max. process pressure (static) 500 bar (7252 psi)
- Maximum standard immersion length 24"

**Field of application:** The robust thermowell is designed for use in demanding and safety relevant applications e.g. in the Chemical, Oil & Gas and Energy industry. Harsh environments, corrosive substances and highest pressures can be handled by the use of robust protection tubes and special materials.

# Features and specifications

#### Thermowell

#### Measuring principle

Bar stock Thermowell

#### Characteristic / Application

US-style

flanged process connections

#### Thermowell

#### **Head connection**

internal thread:

1/2" NPT

#### Maximum standard immersion length

24"

#### **Process connection**

flange

ASME 1" 150 RF (B16.5)

ASME 1" 300 RF (B16.5)

ASME 1" 600 RF (B16.5)

ASME 1" 900/1500 RF (B16.5)

ASME 1.5" 150 RF (B16.5)

ASME 1.5" 300 RF (B16.5)

ASME 1.5" 600 RF (B16.5)

ASME 1.5" 900/1500 RF

(B16.5)

ASME 2" 150 RF (B16.5)

ASME 2" 300 RF (B16.5)

ASME 2" 600 RF (B16.5)

ASME 2" 900/1500 RF (B16.5)

ASME 3" 150 RF (B16.5)

ASME 3" 300 RF (B16.5)

ASME 3" 600 RF (B16.5)

#### Thermowell root diameter

3/4"

7/8"

1 1/16"

#### Medium contact material

316/316L

304

others on request

## Wetted part finishing (Ra)

32 μin (0.80 μin)

#### Thermowell

# Tip shape

straight tapered stepped

# Temperature range

-200...700 °C (-328...1.292 °F)

#### Max. process pressure (static)

500 bar (7252 psi)

# Max. process pressure at 400 °C

depends on configuration

More information www.endress.com/TU54