iTEMP TMT72 Temperature transmitter

Transformation of sensor signals into stable and standardized output signals for all industries



Benefits:

- Safe operation in hazardous areas thanks to international approvals
- Reliable operation thanks to sensor and device monitoring
- Integrated Bluetooth[®] interface for the wireless display of measured values and configuration via E+H SmartBlue (app), optional
- Diagnostics information according to NAMUR NE 107
- Available with plug-on display TID10
- Optimization of the measurement accuracy by sensor-transmitter matching.

Specs at a glance

Accuracy (Pt100, -50...200 °C) <= 0,1 K (Pt100, -58...392 °F) <= 0,18 °F

More information and current pricing: www.endress.com/TMT72

Field of application: Unsurpassed reliability, accuracy and long-term stability in critical processes across all industries. The configurable transmitter transfers converted signals from RTD and thermocouple (TC) temperature probes, as well as resistance and voltage signals using HART[®] communication. Diagnostics information according to NAMUR NE 107. Seamless integration into all major control and asset management systems. Integrated Bluetooth[®] interface for remote operation via Endress+Hauser SmartBlue App.

Features and specifications



Temperature transmitters

Measuring principle

Head transmitter

Input

1 x RTD, TC, Ohm, mV

Output

1 x analog 4...20 mA

Auxiliary power supply

10...36 V DC (Head transmitter) 11...36 V DC (DIN rail device) 10/11...30 V DC (Ex-version)

Communication

HART-protocol Bluetooth[®] wireless technology

Installation

Terminal head form B / DIN rail / in field

Accuracy

(Pt100, -50...200 °C) <= 0,1 K (Pt100, -58...392 °F) <= 0,18 °F

Galvanic isolation

yes

Certification

ATEX CSA C/US General Purpose CSA C/US IS CSA C/US XP EAC IECEx INMETRO NEPSI ATEX IECEx Temperature transmitters

More information www.endress.com/TMT72

