G9400 Series / **HVAC METER**

GAZELLE G9402 Mini Contact Type Thermometer

The G9402 dual-input digital thermometer delivers a fast response. Designed to measure two contact temperature inputs simultaneously, whether measuring motors, insulation, pipes, liquids, and wires with industrial standard J, K-type thermocouple temperature sensors. The user friendly-front panel and large, backlit display make it easy to view results from both channels.



- 1m drop proof
- Maximum/minimum/average
- LCD backlight
- K/J thermocouple probe selection
- Difference measurement: T1~T2
- CE Certified







| Specifications | | |
|--------------------------------|--------------|---------------|
| Model | Range | Best Accuracy |
| Temperature measurement (K) | -50~1300°C | ±(0.5%+1) |
| Temperature measurement (J) | -50~1200°C | ±(0.5%+1) |
| Features | | |
| Difference measurement (T1-T2) | \checkmark | |
| Unit conversion (°C/°F) | V | |
| Max/Min/Avg | \checkmark | |
| Function selection (K/J) | \checkmark | |
| Backlight | \checkmark | |
| Working temperature | 0°C~40°C | |
| Working humidity (relative) | ≤80%RH | |
| 1m drop test | \checkmark | |
| Power | 3 x AAA | |

Standard Accessories

- Operating Manual
- Temperature Probe
- 1.5V AAA 3pcs



