

SPECIFICATIONS

Basic Functions	Range	Accuracy
DC Voltage	50mV/500mV/5V/50V/500V/1000V	$\pm(0.03\%+10)$
AC Voltage	50mV/500mV/5V/50V/500V/1000V	$\pm(0.5\%+40)$
DC Current	500 μ A/5000 μ A/50mA/500mA/5A/10A	$\pm(0.15\%+15)$
AC Current	500 μ A/5000 μ A/50mA/500mA/5A/10A	$\pm(0.75\%+20)$
Resistance	500 Ω /5K Ω /50K Ω /500K Ω /5M Ω 50M Ω	$(\pm 0.1\%+10)$ $(\pm 0.5\%+10)$
Capacitance	50nF/500nF/5 μ F/50 μ F 500 μ F/5000 μ F	$\pm(1\%+5)$ $\pm(2\%+5)$
Line Frequency	5Hz~200KHz	$\pm(0.006\%+4)$
Pulse Frequency	5Hz~2MHz	$\pm(0.006\%+4)$
Duty Cycle	5%~95%	$\pm(2\%+5)$
Diode	0~2.5V	$\pm(1\%+5)$

Special Functions:

Display: 50000 counts

True RMS Measurement DC/AC/DC+AC Measure

Diode test

Duty Cycle

Back Light

360°Directions Display

General Characteristics

Power : 1.5V AAA *6

LCD Size: 64x42

Product Size: 205x97x45

Standard Individual Packing: Gift Box

- | |
|---|
| ● Free 1.5 x6 AAA batteries |
| ● Free carrying bag |
| ● High quality double insulation test leads |
| ● User's manual |
| ● Free USB interface cable |
| ● Free software |

