## Model: HT6510F

Durometer Type F is an exclusive design for testing soft cellular materials. The large diameter presser foot and cylindrical indentor configuration allow measurement by direct application to the test specimen.

## **SPECIFICATIONS**

Display: 4 digits, 10 mm LCD

Range: 0~100 Resolution: 0.1

Presser foot: 80mm diameter

Indenter: Extension 2.54mm 25.2mm Cylinder

Spring force: 455gf

Measurement deviation:  $= \pm 1$ 

Power supply: 4x1.5v AA (UM-3) battery

Operating condition: Temp. 0~50? Humidity <80%

Size: 162x65x28mm (6.4x2.6x1.1inch)

Weight: about 490g (not including batteries)

PC interface: RS232C interface

Power off: 2 modes

Manual off at any time by depressing the power key till OFF shows on the display or Auto power off after 2 minutes from last key operation.

Accessories:

Carrying case 1 pc.

Operation manual 1 pc.



Navtek Instruments India Private Limited

001/C-57 Sector -10, Shanti Nagar,

Mira Road (east) – 401107 (MUMBAI – MAHARASHTRA)

**INDIA** 

TEL: 91-22-28128507 / 28101326

 $e\text{-}mail: \underline{info@navtekinstruments.com}; \underline{purchase@navtekinstruments.com}$ 

