

## Videoscope PCE-VE 270SV with side view camera



Battery-operated videoscope with 3 mm (0.11") diameter / For inspecting motors and machine parts / Memory / HDMI output / Various camera cables

The videoscope with side view camera gives you new, visual insights into the interior of motors and systems. The inspection camera is the ideal tool for maintenance and repair in workshops or industrial companies. Optical analysis with an inspection camera has never been so easy. Guide the flexible cable through a hole or a cavity near the point to be inspected and look at everything on the display from the inspection camera. Thanks to the flexible guidance, the low weight and the excellent optics, you can use this inspection camera to identify weak spots and problem areas very easily and early and thus take preventive measures without having to carry out complex disassembly first.

This videoscope with side view camera is extremely versatile, particularly due to the length of the flexible part (2000 mm / 6.56 ft) and the small diameter of 3 mm / 0.11". LEDs on the inspection camera illuminate the cavities. The waterproof lens and camera can also be used in liquids without hesitation. Make your daily work easier and use the inspection camera for the maintenance and inspection of your operational systems and machines. The inspection camera can be used to save images and videos for documentation on a memory card. The inspection camera can be connected to a monitor via the HDMI interface.

- > 2 m / 6.56 ft cable length
- ▶ 3 mm / 0.11" cable diameter
- ▶ Storage function on micro SD card
- ▶ LED light
- ▶ 90° side viewing angle

## **Specifications**

Cable length 2000 mm / 6.56 ft

Cable type flexible
Cable diameter 3 mm / 0.11"

Degree of protection IP 67

Depth of field of view 5 ... 50 mm / 0.2 ... 1.98"

Field of view 120°

Angle of view side 90°

Lighting 2 LEDs

Exposure automatic

Anti-reflective coating automatic

Image sensor 1/18" CMOS

Camera resolution / image sensor 400 x 400 Px

Display 5" TFT screen
Interface Micro-USB, HDMI
Storage option Image and video

Storage Micro SD memory card Picture format JPEG ( $400 \times 400 \text{ Px}$ ) Video format MP4 ( $400 \times 400 \text{ Px}$ )

Video output HDMI

Menu navigation German, English, Chinese, Spanish,

Portuguese,

French, Russian, Japanese, Korean

Operating and storage temperature -10 ... +50 °C / 14 ... 122 °F

Power supply 3.7 V Li-ion battery, 5200 mAh

Battery life min. 6 h

Dimensions 200 x 130 x 58 mm / 7.9 x 5.1 x 2.3"

Weight 595 g / 1.3 lb

## More information

Manual



More product info



**Similar products** 

